


150-2010

Irrax Sleeve SCM2 & Sumitube W3F2



	Cat. No.	I. D.	Thickness	Shrinking	Std. Pkg.
		φ mm	After Shrinkage mm	Range φ mm	
Industry series	SCM2 - 04	10.2	1.5	10.2 ~ 3.8	1.22
	SCM2 - 07	19	2	19 ~ 5.6	
	SCM2 - 11	28	2	28 ~ 9.5	
	SCM2 - 13	33	2	33 ~ 10.2	
	SCM2 - 15	38.1	2.3	38.1 ~ 12.7	
	SCM2 - 17	44	2.3	44 ~ 14	
	SCM2 - 20	52	2.3	52 ~ 18.2	
	SCM2 - 27	70	2.3	70 ~ 25.5	
	SCM2 - 35	90	2.3	90 ~ 30	
Electric series	W3F2 - 1/8	3.2	0.95	3.2 ~ 0.6	1.22
	W3F2 - 3/16	4.8	1.1	4.8 ~ 1.5	
	W3F2 - 1/4	6.4	1.2	6.4 ~ 2	
	W3F2 - 3/8	9.5	1.3	9.5 ~ 3	
	W3F2 - 1/2	12.7	1.4	12.7 ~ 4	
	W3F2 - 3/4	19	1.6	19 ~ 8	
	W3F2 - 1	25.4	1.9	25.4 ~ 10.2	

IRRAX SLEEVE SCM2

- Material : polyolefin resin cross-linked by electron beam with hot-melt adhesive inside.
- Working temperature : - 55 °C to 120 °C (- 67 °F to 248 °F).
- Voltage rating : 600 V.
- Encapsulation and insulation of joints of connectors and terminations of low-pressure cables and telecommunication equipment.
- Encapsulation and insulation of joints of connectors and cables.
- Anticorrosion of joints of pipes.
- Substitution of taping mold treatment.

SUMITUBE W3F2


- FLEXIBLE PROTECTIVE SHEATH
- Material : Cross-linked polyolefin resin for tube with hot-melt adhesive inside. (flame-retardant)
 - Working temperature : - 55 °C to 125 °C (- 67 °F to 257 °F).
 - Voltage rating : 600 V.
 - Protection of irregularly shaped electric parts against water.
 - Insulation protection of electric joints.
 - Effective encapsulation of irregularly shaped objects to be covered.

150-3010

PVC Heat Shrinkable Tubings



Conversion :
 Inner D. : Folding D. ÷ 1.57
 Folding D. : Inner D. x 1.57



Cat. No.	Folding Dia. mm	Inner Dia. φ mm	Shrinking Range mm	Applicable Busbar Sizes mm	Colors	Std. Pkg.
						M
H - 6.5	6.5	4.1	6.5 ~ 3.6	-	Red White Blue Yellow Black Green	100
H - 8.5	8.5	5.2	8.5 ~ 5	-		
H - 12	12	7.6	12 ~ 6.5	-		
H - 16	16	10	16 ~ 8.5	12x2		
H - 21	21	13	21 ~ 11	12x3 , 15x2, 15x3		
H - 30	30	19	30 ~ 16	20x3 , 20x5, 25x3		
H - 40	40	25	40 ~ 22	25x5 , 30x3, 30x5		
H - 50	50	31	50 ~ 27	30x10, 40x5, 40x8		
H - 60	60	38	60 ~ 32	40x10, 50x5, 50x8		
H - 70	70	44	70 ~ 37	50x10, 60x5, 60x8		
H - 80	80	50	80 ~ 42	60x10		
H - 100	100	63	100 ~ 55	80x6 , 80x8, 80x10		
H - 120	120	76	120 ~ 65	100x6 , 100x8, 100x10		
H - 150	150	95	150 ~ 90	-		
H - 170	170	108	170 ~ 100	150x10		
H - 200	200	127	200 ~ 110	-		

- Material : Hard PVC.
- Application : Color identification for electrical bus bar or for packaging purpose.